Industrial Pressure Transmitter

Model: PT124B-215 (Explosion proof)




Description

PT124B-215 is With stainless steel welding encapsulated component and lightning proof isolation device, all welding with Explosion Proof grade : EXialICT4/ 6, it has the character of corrosion proof, wide range temperature compensation, excellent linearity and diversifying output signal .This series can be suitable for liquid , water,Oil,Air,Petroleum , natural gas,coal or mine etc for explosion proof in hazard fields.



Dimension



编	북 α	b	c	d	
М	M14X1.5	M20X1.5	G1/4	G1/2	
D	Ø19	Ø25	Ø19	Ø25	



Specification

Range	-1 ~ 0~6000bar		
Accuracy	0.25%FS; 0.5%FS		
Nonlinearity	0.2%FS		
Reliability	0.05%FS		
Output	4-20mA (2 Wire) , 0-5V; 0-10V, 0.5-4.5V		
Input voltage	24(12~36)VDC (Amplify signal)		
Work Temperature Range	-40~80℃		
Compensated temp range	0~70℃		
Overload pressure	150%FS		
Medium material	stainless steel		
Electric connection	4 pins , 1/2NPT cable , gland cable		
Pressure connection	G1/4, G1/2, 1/2NPT, 1/4NPT, M12*1.5,etc(Customer design)		

Electric Connection									
Electric connector	2	2 wire(4-20mA)			3 wire (0-10V, 0-5V, 0.5-4.5V)				
M12,4Pin	Pin	Fun	ction	Color	Pin Func		oction	Color	
	1	E+		Brown	1	E+		Brown	
$\left(\begin{pmatrix} 0 & 1 \\ 2 & 0 & 04 \end{pmatrix} \right)$	2	-			2	-			
30	3	E	+	Blue	3	S+		Blue	
	4	-			4	E-/S-		White	
1/2NPT cable	Funct	ion		Color	Function		Color		
	E+		Red		E+		Red		
	S+		Black		S+		Blue		
					E-/S-		White		
Gland Cable	E+			Red	d E+		Red		
	S+	S+		Black		S+		Blue	
					E-/S	-		White	

Ordering Guide

Model	Range(bar)	Output	Screw	Electric	Other requirement		
			Thread	connection			
PT124B-215							
Example: PT124B-215-50Bar-4/20mA-G1/2- M12							

Shanghai Zhaohui Pressure Apparatus Co., Ltd.

5-6F No.8 Building No.115, Lane 1276 Nanle Road Songjiang District Shanghai 201600 China Tel:+86-21-51691919 67755189 Fax:+86-21-67755185 E-mail: info@zhyqsensor.com www.zhyqsensor.com

